

ANQA PUTTY

Solvent Free, Epoxy Flooring Top Coat

Ⓜ www.anqa.com.sa ✉ @anqa_com_sa 📷 [@anqa.com.sa](https://www.facebook.com/anqa.com.sa)



DESCRIPTION:

Anqa-Putty is a ready-mix putty composed of vinyl polymers and a water-based formula. It is a non-toxic, non-flammable material used to smooth uneven cement and wooden surfaces, creating a flat and smooth finish that is easy to sand and ideal for paint application.

FEATURES:

- Ready to use; easily applied with a filling knife, spoon, or shovel
- Excellent adhesion on both interior and exterior concrete surfaces
- Suitable for application on wooden surfaces
- Free from harmful solvents; easy to clean tools after use
- Easy application on vertical and horizontal surfaces using a filling knife or spatula
- Flexible and resistant to cracking at low temperatures
- Excellent coverage properties

APPLICATION METHOD:

Mixing:

Mix the paste manually or mechanically to ensure homogeneity. Do not add water or any other substances.

Surface Preparation:

Clean the surface thoroughly to remove dust, debris, grease, and oils. It is recommended to moisten the surface with water before application. Ensure the ambient temperature is between 5°C and 40°C.

Application:

Apply the product using a knife or suitable tool.

- Apply the first coat and allow it to dry for 4–6 hours, depending on weather conditions.
- Apply one to three coats as needed.
- Sand the surface after each coat has fully dried.

STORAGE & SHELF LIFE:

Store in sealed containers under suitable conditions. Shelf life is 12 months. Use packages with the oldest production date first.

COVERAGE:

Approximately 1.8 m²/kg for two coats.

TECHNICAL SPECIFICATION

SPECIFICATIONS	STD	ANQA-PUTTY
Physical Appearance		White creamy putty
Viscosity	ASTM D 2196	140000 – 150000 CPs
Solid Content %	ASTM D4541	70 - 75
Specific Density	ASTM D1475	1.6 – 1.75
PH	PH ASTM D 1172	8-9